

## PNEUMATIC STEEL STRAPPING TOOL WITH SEAL JOINT



### TECHNICAL SPECIFICATIONS

#### DIMENSIONS

Length	350mm • 13.8"
Width	140 mm • 5.5"
Height	170 mm • 6.7"
Weight	4 Kgs • 8.8 lbs

#### FEEDING

Pressure range	5.5 - 7 bar / 78-99 psi
Air consumption	12 L/s - 25 cuft/min

#### PERFORMANCE

Max. tension force	2000 N - 5500 N - 7500 N 6 bar - 87 psi
Tensioning speed	12mt/m @ 2000 N 5 mt/m @ 5500 N 4 mt/m @ 7500 N
Sealing	Seal single notch
Joint strength	80% of breaking strength*

\* variable according to strap type

### MODEL

CODE	TYPE	STRAP	THICKNESS
T401311	ITA40 - 13mm-1/2" -2000N	R 850N/mm <sup>2</sup>	0.4mm - 0.8mm
		R 1100N/mm <sup>2</sup>	0.4mm - 0.63mm
T401611	ITA40 - 16mm-5/8" -2000N	R 850N/mm <sup>2</sup>	0.4mm - 0.8mm
		R 1100N/mm <sup>2</sup>	0.4mm - 0.63mm
T401911	ITA40 - 19mm-3/4" -2000N	R 850N/mm <sup>2</sup>	0.4mm - 0.8mm
		R 1100N/mm <sup>2</sup>	0.4mm - 0.63mm
T401321	ITA40 - 13mm-1/2" -5500N	R 850N/mm <sup>2</sup>	0.4mm - 0.8mm
		R 1100N/mm <sup>2</sup>	0.4mm - 0.63mm
T401621	ITA40 - 16mm-5/8" -5500N	R 850N/mm <sup>2</sup>	0.4mm - 0.8mm
		R 1100N/mm <sup>2</sup>	0.4mm - 0.63mm
T401921	ITA40 - 19mm-3/4" -5500N	R 850N/mm <sup>2</sup>	0.4mm - 0.8mm
		R 1100N/mm <sup>2</sup>	0.4mm - 0.63mm
T401331	ITA40 - 13mm-1/2" -7500N	R 850N/mm <sup>2</sup>	0.4mm - 0.8mm
		R 1100N/mm <sup>2</sup>	0.4mm - 0.63mm
T401631	ITA40 - 16mm-5/8" -7500N	R 850N/mm <sup>2</sup>	0.4mm - 0.8mm
		R 1100N/mm <sup>2</sup>	0.4mm - 0.63mm
T401931	ITA40 - 19mm-3/4" -7500N	R 850N/mm <sup>2</sup>	0.4mm - 0.8mm
		R 1100N/mm <sup>2</sup>	0.4mm - 0.63mm

### SEAL SINGLE NOTCH

