

PNEUMATIC STEEL STRAPPING TOOL WITH WITH SEAL, UPCUT JOINT



TECHNICAL SPECIFICATIONS	
DIMENSIONS	
Length	430mm • 16.9"
Width	260mm • 10.2"
Height	310mm • 12.2"
Weight	11.3 kgs • 25lbs
FEEDING	
Pressure range	5.5 -7 bar / 78 -99 psi
Air consumption	12 L/s - 25 cuft/min
PERFORMANCE	
Max. tension force	9000 N - 15000 N 6 bar - 87 psi
Tensioning speed	4,5 mt/m @ 9000 N 4 mt/m @ 15000 N
Sealing	Seal double notches
Joint strength	80% of breaking strength*

* variable according to strap type

MODEL			
CODE	TYPE	STRAP	THICKNESS
T521943	ITA52-19mm-9000N- 2B	R 850N/mm ²	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm ²	0.63mm 0.025" - 0.8mm 0.031"
T522543	ITA52-25mm-15000N- 2B	R 850N/mm ²	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm ²	0.63mm 0.025" - 0.8mm 0.031"
T523243	ITA52-32mm-15000N- 2B	R 850N/mm ²	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm ²	0.63mm 0.025" - 0.8mm 0.031"

SEAL DOUBLE NOTCHES

